

LUIGINO

TSP



elevate to **PROFESSIONAL**



Compact and reliable with professional heart

Compact design that well integrates into every environment, offering performance comparable to professional products.

A PRO GRADE compact machine entirely made in Stainless steel, with professional components. Double Independent taps for steam and hot water for espresso and cappuccino lovers. Electronic Water level control. 1,5 lt boiler with internal heat exchanger that allows the simultaneous delivery of Espresso, Steam and hot water just like at the bar. **PID Temperatures control and double pressure gauge to display boiler pressure and pump pressure.**

Maximum versatility, professional performances, and thermal stability thanks to the E61 group with a new ergonomic and elegant dispensing lever ERGO-LIFT.



TSP Torre Smart Pid

The Exclusive new Torre smart control to manage all the primary functions of your machine. It gives you complete control on your espresso experience

Premium Equipment

Top-Tier standard features that comes with your Luigino

Always included:

Single spout filter holder
Double spout filter holder
Cleaning cloth
Spoon
Tamper

E61 group with thermosiphonic circulation
ERGO-LIFT dispensing lever
Stainless steel frame
Vibration pump low noise
Steam tap with cold touch wand (*Joystick option*)
Water tap with cold touch wand (*Joystick option*)
1500cc Copper boiler with internal exchanger
1100W heating element power

Electronic level
Boiler pressure gauge
Pump pressure gauge
Relay SSR power (*great reliability*)
Large removable cup warmer top with stainless steel cup rail
Removable tank with sensor
Removable drip tray

Optional Dotation

Top-Tier variations

Available in version with stainless steel rotary pump

Also available with Wood knobs version

ELEVATE YOUR STYLE

Exclusive TSP Torre Smart Pid with oled display and action button

Four different temperatures setting with PID control.

Adjustable electronic pre infusion.

Adjustable ECO modus.

Steam Boost Functions to obtain maximum steam in all conditions.

Shot timer.

Anti overheat algorithm integrated.

Intelligent tank level alarm (even with an empty tank the machine remains warm, just fill the tank without having to wait for it to heat up).



Technical features

main supply	heating	boiler	pump	feeding	width	depth	height	weight
110-120Vac / 50-60 Hz 220-240Vac / 50-60 Hz	2x1100 W	1,5 lt	vibration or rotary	Tank 2,4 lt/Net	260 mm	410 mm	385 mm	20,5 kg (Vibration pump) 22,5 kg (Rotary pump)