

MARIUCCIA



always
DELIVER



**High technology
and premium finishes**

Two separate boilers to be able to deliver espresso and steam independently, without altering the thermal equilibrium also severe working conditions, thanks also to the volumetric pump and the possibility of direct connection to the water mains.

AISI316 stainless steel water / steam boiler controlled by pressure switch, with exclusion switch for energy saving. AISI 316 stainless steel coffee boiler with temperature control managed by a PID thermostat, which allows you to adjust the temperature of the water supplied by the group in a range from 80 to 100 degrees ° C in order **to optimize extraction according to the different types of coffee and different roasts**, while maintaining constant thermal stability.



Premium finishes

Torre trademark, superlative design and extreme attention to every detail

Premium Equipment Top-Tier standard features that comes with your Mariuccia

E61 group with thermosiphonic circulation
ERGO-LIFT dispensing lever
Volumetric pump
Professional Joystick Steam tap
with cold touch wand
Professional Joystick hot water tap
with cold touch wand
Aisi 316 stainless steel water/steam boiler
1,4 lt. improved capacity
Aisi 316 stainless steel coffee boiler 0,75 lt.

Electronic water level
PID electronic thermostat new design
CHRONO function
Boiler pressure gauge
Pump pressure gauge
Large removable cup warmer surface
Removable tank
Possibility of direct water connection
Removable drip tray
Stainless steel frame

Premium Dotation Top-Tier premium accessories

Also available with Wood knobs version

THE BEST EXTRACTION

Exclusive Torre Steam pro balance to manage the water level in the steam boiler

Chrono function during delivery, which allows the user to monitor the timing of extractions

Double independent tap for steam and hot water for lovers of espresso and cappuccino

Water level in the boiler managed electronically.

Double pressure gauge to display boiler pressure and pump pressure and pressure.

Maximum versatility, professional performances and thermal stability thanks to the E61 group with a new ergonomic and elegant design dispensing lever ERGO-LIFT



Technical features

main supply	heating	boilers	pump	feeding	width	depth	height	weight
110-120Vac / 50-60 Hz 220-240Vac / 50-60 Hz	1100 W 1400 W	0,75 + 1,5 lt	volumetric	Tank 2,4 lt/Net	325 mm	440 mm	405 mm	29 kg