

TERESINA

TIMER



professional PERFORMANCES



Professional-grade MODEL with chrono function

A domestic machine entirely made in Stainless steel, with professional components and premium line finishing.

Double tap Independent steam and hot water for espresso and cappuccino lovers, Electronic Water level control. Large 2.3lt boiler with internal heat exchanger that allows the simultaneous delivery of Espresso, Steam and hot water just like at the bar. The large boiler makes this machine usable also by small bars and catering. Pressure control with pressure switch and double pressure gauge to display boiler pressure and pump pressure.

Maximum versatility, professional performances and thermal stability thanks to the E61 group with a new ergonomic and elegant design dispensing lever ERGO-LIFT.

Oled display

Oled Display with integrated functions:
Shot timer.
Adjustable electronic pre infusion.
Adjustable ECO modus.



Premium Equipment Top-Tier standard features that comes with your Teresina

E61 group with thermosiphonic circulation
ERGO-LIFT dispensing lever
Vibration pump
Joystick steam tap with cold touch wand
Joystick water tap with cold touch wand
2300cc Aisi 316 stainless steel boiler
with internal heat exchanger

Boiler pressure gauge
Pump pressure gauge
Relay SSR power (great reliability)
Large removable cup warmer top
Removable tank with sensor
Removable drip tray
Stainless steel frame

Optional Dotation Top-Tier variations

Available in RS version with volumetric
pump with direct net connection

Also available with aluminum
style feet machined from billet

ESPRESSO LIKE A PRO

Professional-grade performances a machine with premium finishes and component

CHRONO function during delivery allows the user to monitor the timing of extraction. Maximum versatility, professional performances and thermal stability thanks to the E61 group with a new ergonomic and elegant design dispensing lever ERGO-LIFT.



Technical features

main supply	heating	boiler	pump	feeding	width	depth	height	weight
110-120Vac / 50-60 Hz 220-240Vac / 50-60 Hz	2x1400 W	2,3 lt	vibration / rotary (RS)	Tank 2,4 lt/Net	325 mm	440 mm	405 mm	24 kg (std.) 27,7 kg (RS)